

ABSTRACT OF THE DISCLOSURE

A method for converting a real signal into a complex signal inherently in quadrature, whose particularity consists of the fact that it comprises the step that consists in adding to a real signal meant to be converted into a complex  
5 signal a signal whose frequency is four times the band-center frequency of the signal to be converted, in order to obtain an inherent quadrature.

FIG. 1  
FIG. 2  
FIG. 3  
FIG. 4  
FIG. 5  
FIG. 6  
FIG. 7  
FIG. 8  
FIG. 9  
FIG. 10  
FIG. 11  
FIG. 12  
FIG. 13  
FIG. 14  
FIG. 15  
FIG. 16  
FIG. 17  
FIG. 18  
FIG. 19  
FIG. 20  
FIG. 21  
FIG. 22  
FIG. 23  
FIG. 24  
FIG. 25  
FIG. 26  
FIG. 27  
FIG. 28  
FIG. 29  
FIG. 30  
FIG. 31  
FIG. 32  
FIG. 33  
FIG. 34  
FIG. 35  
FIG. 36  
FIG. 37  
FIG. 38  
FIG. 39  
FIG. 40  
FIG. 41  
FIG. 42  
FIG. 43  
FIG. 44  
FIG. 45  
FIG. 46  
FIG. 47  
FIG. 48  
FIG. 49  
FIG. 50  
FIG. 51  
FIG. 52  
FIG. 53  
FIG. 54  
FIG. 55  
FIG. 56  
FIG. 57  
FIG. 58  
FIG. 59  
FIG. 60  
FIG. 61  
FIG. 62  
FIG. 63  
FIG. 64  
FIG. 65  
FIG. 66  
FIG. 67  
FIG. 68  
FIG. 69  
FIG. 70  
FIG. 71  
FIG. 72  
FIG. 73  
FIG. 74  
FIG. 75  
FIG. 76  
FIG. 77  
FIG. 78  
FIG. 79  
FIG. 80  
FIG. 81  
FIG. 82  
FIG. 83  
FIG. 84  
FIG. 85  
FIG. 86  
FIG. 87  
FIG. 88  
FIG. 89  
FIG. 90  
FIG. 91  
FIG. 92  
FIG. 93  
FIG. 94  
FIG. 95  
FIG. 96  
FIG. 97  
FIG. 98  
FIG. 99  
FIG. 100